Safety data sheet

as per regulation 1907/2006/EC (REACH) as amended and supplemented

Printing date 17.10.2019 *Version number 166* *Revision: 17.10.2019*

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· **1.1 Product identifier**

· **Product code** LNB837

· **Trade name: POLYURETHANE HARDENER**

· **1.2. Relevant identified uses of the substance or mixture and uses advised against**

Paint and relative material only for wood

· **Application of the substance / the mixture** For professional use

· **1.3 Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

IVM Chemicals srl

Viale della Stazione 3 - 27020 Parona (PV) Italy tel +39 038425441

· **Further information obtainable from:**

Environmental Health and safety office

hseoffice@ivmchemicals.com

· **1.4 Emergency telephone number:**

From 8.30 to 17.30 0039 038 425 441

Out of the above mentioned hours, Saturdays and Sundays and during periods of closure for holidays please call: 0039 0384 254491

SECTION 2: Hazards identification

· **2.1 Classification of the substance or mixture**

· **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 2	H225	Highly flammable liquid and vapour.



GHS08 health hazard

Resp. Sens. 1	H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Repr. 2	H361d	Suspected of damaging the unborn child.
STOT RE 2	H373	May cause damage to organs through prolonged or repeated exposure.
Asp. Tox. 1	H304	May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2	H315	Causes skin irritation.
Eye Irrit. 2	H319	Causes serious eye irritation.
Skin Sens. 1	H317	May cause an allergic skin reaction.
STOT SE 3	H336	May cause drowsiness or dizziness.
Aquatic Chronic 3	H412	Harmful to aquatic life with long lasting effects.

· **2.2 Label elements**

· **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

Safety data sheet
as per regulation 1907/2006/EC (REACH) as amended and supplemented

Printing date 17.10.2019 *Version number 166* *Revision: 17.10.2019*

Product code LNB837
Trade name: POLYURETHANE HARDENER

(Contd. of page 1)

· ***Hazard pictograms***



GHS02 GHS07 GHS08

· ***Signal word*** Danger

· ***Hazard-determining components of labelling:***
toluene
Aromatic polyisocyanate
m-tolylidene diisocyanate
isobutyl acetate

· ***Hazard statements***
H225 Highly flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317 May cause an allergic skin reaction.
H361d Suspected of damaging the unborn child.
H336 May cause drowsiness or dizziness.
H373 May cause damage to organs through prolonged or repeated exposure.
H304 May be fatal if swallowed and enters airways.
H412 Harmful to aquatic life with long lasting effects.

· ***Precautionary statements***
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P241 Use explosion-proof electrical/ventilating/lighting equipment.
P260 Do not breathe vapours.
P284 [In case of inadequate ventilation] wear respiratory protection.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P321 Specific treatment (see on this label).
P331 Do NOT induce vomiting.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P362+P364 Take off contaminated clothing and wash it before reuse.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local.

· ***Additional information:***
EUH204 Contains isocyanates. May produce an allergic reaction.

· **2.3 Other hazards**
· ***Results of PBT and vPvB assessment***
· ***PBT:*** *Not applicable.*
· ***vPvB:*** *Not applicable.*

SECTION 3: Composition/information on ingredients

· **3.2 Chemical characterisation: Mixtures**
· ***Description:*** *Mixture: consisting of the following components.*

(Contd. on page 3)

Safety data sheet
as per regulation 1907/2006/EC (REACH) as amended and supplemented

Printing date 17.10.2019 *Version number 166* *Revision: 17.10.2019*

Product code LNB837
Trade name: POLYURETHANE HARDENER

(Contd. of page 2)

· ***Dangerous components:***

CAS: 108-88-3 EINECS: 203-625-9 Reg.nr.: 01-2119471310-51-XXXX	toluene Flam. Liq. 2, H225 Repr. 2, H361d; STOT RE 2, H373; Asp. Tox. 1, H304 Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H336 Aquatic Chronic 3, H412	30-49.99%
CAS: 53317-61-6	Aromatic polyisocyanate Eye Irrit. 2, H319; Skin Sens. 1, H317	25-29.99%
CAS: 110-19-0 EINECS: 203-745-1 Reg.nr.: 01-2119488971-22-XXXX	isobutyl acetate Flam. Liq. 2, H225 STOT SE 3, H336	20-24.99%
CAS: 141-78-6 EINECS: 205-500-4 Reg.nr.: 01-2119475103-46-XXXX	ethyl acetate Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336	10-12.49%
CAS: 26471-62-5 EINECS: 247-722-4 Reg.nr.: 01-2119454791-34-XXXX	m-tolylidene diisocyanate Acute Tox. 2, H330 Resp. Sens. 1, H334; Carc. 2, H351 Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335 Aquatic Chronic 3, H412	≥0.1-<0.5%

· ***Additional information:*** *For the wording of the listed hazard phrases refer to section 16.*

SECTION 4: First aid measures

· ***4.1 Description of first aid measures***

· ***General information:***
Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
personal protective equipment for first aid responders is recommended. (please see section 8)

· ***After inhalation:***
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.

· ***After skin contact:***
Remove contaminated clothing.
Immediately wash with water and soap, or a recognized skin cleanser, and rinse thoroughly.
Take off immediately all contaminated clothing, include underwear and shoes (if necessary).
Rinse thoroughly with plenty of water for at least 20 minutes and take medical advise. I medical advise is needed have products container or label at hand.

· ***After eye contact:***
Rinse opened eye for several minutes under running water. Then consult a doctor.

· ***After swallowing:*** *Do not induce vomiting; call for medical help immediately.*

· ***4.2 Most important symptoms and effects, both acute and delayed***
For symptoms and effects caused by substances, see chap. 11th
No further relevant information available.

· ***4.3 Indication of any immediate medical attention and special treatment needed***
No further relevant information available.

(Contd. on page 4)

ivm Chemicals
coatings & polymers technologies

Safety data sheet
as per regulation 1907/2006/EC (REACH) as amended and supplemented

Printing date 17.10.2019 Version number 166 Revision: 17.10.2019

Product code LNB837
Trade name: POLYURETHANE HARDENER

(Contd. of page 3)

SECTION 5: Firefighting measures

· **5.1 Extinguishing media**
· **Suitable extinguishing agents:** Alcohol resistant foam, CO, powder, water spray/mist.
· **For safety reasons unsuitable extinguishing agents:**
Do not use a jet water stream as it may scatter and spread fire.
· **5.2 Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
· **5.3 Advice for firefighters**
Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.
· **Protective equipment:**
Hardhat with visor, fireproof clothing, suitable gloves and if necessary mouth respiratory protective device.

SECTION 6: Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
Keep away from ignition sources.
· **6.2 Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
· **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
· **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

· **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
Protect against electrostatic charges.
Keep respiratory protective device available.
Use explosion-proof apparatus / fittings and spark-proof tools.
· **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.

(Contd. on page 5)

(Contd. of page 4)

· **7.2 Conditions for safe storage, including any incompatibilities**
· **Storage:**
· **Requirements to be met by storerooms and receptacles:**
Store in a cool, well-ventilated area, away from heat and sources of ignition
Provide solvent resistant, sealed floor.
Observe the label precautions, the expiration date for the use, if indicated, is from delivery date.
In cases there is no reported deadline, it means that the product must be used within 8 months.
· **Information about storage in one common storage facility:** Not required.
· **Further information about storage conditions:**
Keep container tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
· **7.3 Specific end use(s)**
Those typical of the product and the instructions in the data sheet if required.

*
SECTION 8: Exposure controls/personal protection

· **Additional information about design of technical facilities:** No further data; see item 7.

· **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**	
141-78-6 ethyl acetate (10-12.49%)	
WEL	Short-term value: 1468 mg/mį, 400 ppm Long-term value: 734 mg/mį, 200 ppm
26471-62-5 m-tolylidene diisocyanate (≥0.1-<0.5%)	
WEL	Short-term value: 0.07 mg/mį Long-term value: 0.02 mg/mį Sen; as -NCO

· **DNELs**		
108-88-3 toluene		
Inhalative	DNEL acuto/agudo/ostre/aigu/acute/akut	384 mg/mc (Workers)
	DNEL	192 mg/mc (Workers)
Irritation of skin	DNEL	384 mg/kg bw/d (Workers)
110-19-0 isobutyl acetate		
Oral	DNEL	5 mg/kg bw/d (population)
Inhalative	DNEL acuto/agudo/ostre/aigu/acute/akut	600 mg/mc (Workers)
		300 mg/mc (population)
	DNEL	300 mg/mc (Workers)
		35.7 mg/mc (population)
Irritation of skin	DNEL acuto/agudo/ostre/aigu/acute/akut	5 mg/kg bw/d (population)
	DNEL	10 mg/kg bw/d (Workers)
		5 mg/kg bw/d (population)
141-78-6 ethyl acetate		
Oral	DNEL	4.5 mg/kg bw/d (population)
Inhalative	DNEL acuto/agudo/ostre/aigu/acute/akut	1,468 mg/mc (Workers)
		734 mg/mc (population)

(Contd. on page 6)

(Contd. of page 5)

Irritation of skin	*DNEL*	*734 mg/mc (Workers)* *367 mg/mc (population)* *63 mg/kg bw/d (Workers)* *37 mg/kg bw/d (population)*
26471-62-5 m-tolylidene diisocyanate		
Inhalative	*DNEL acuto/agudo/ostre/aigu/acute/akut* *DNEL*	*0.14 mg/mc (Workers)* *35 mg/mc (Workers)*

· ***PNECs***	
108-88-3 toluene	
PNEC Acqua dolce/water/woda słodka/eau/agua/ *PNEC Suolo/earth/suelo/ﾅ嗽ｺ/ﾅ嗽ｺ/*	*0.68 mg/L (_)* *2.89 mg/kg (_)*
110-19-0 isobutyl acetate	
PNEC Acqua dolce/water/woda słodka/eau/agua/ *PNEC Suolo/earth/suelo/ﾅ嗽ｺ/ﾅ嗽ｺ/*	*0.17 mg/L (_)* *0.0755 mg/kg (_)*
141-78-6 ethyl acetate	
PNEC Acqua dolce/water/woda słodka/eau/agua/ *PNEC Suolo/earth/suelo/ﾅ嗽ｺ/ﾅ嗽ｺ/*	*0.24 mg/L (_)* *0.148 mg/kg (_)*
26471-62-5 m-tolylidene diisocyanate	
PNEC Acqua dolce/water/woda słodka/eau/agua/ *PNEC Suolo/earth/suelo/ﾅ嗽ｺ/ﾅ嗽ｺ/*	*13 mg/L (_)* *1.1 mg/kg (_)*

· ***Additional information:*** *The lists valid during the making were used as basis.*

· ***8.2 Exposure controls***

· ***Personal protective equipment:***

· ***General protective and hygienic measures:***
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid contact with the eyes and skin.
Pregnant women should strictly avoid inhalation or skin contact.

· ***Respiratory protection:***
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· ***Protection of hands:***



Protective gloves

The glove material has to be impermeable and resistant to the product and in accordance with EN 374 and Directive 89/686/EEC.
Due to missing tests no recommendation to the glove material can be given for the product.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· ***Material of gloves***
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 7)

ivm Chemicals
coatings & polymers technologies

Safety data sheet
as per regulation 1907/2006/EC (REACH) as amended and supplemented

Printing date 17.10.2019 Version number 166 Revision: 17.10.2019

Product code LNB837
Trade name: POLYURETHANE HARDENER

(Contd. of page 6)

· **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Glasses (EN166) or other protective equipment

*
SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**	
· **General Information**	
· **Appearance:**	
· **Form:**	Fluid
· **Colour:**	According to product specification
· **Odour:**	Characteristic
· **Odour threshold:**	Not determined.
· **pH-value:**	Not determined.
· **Change in condition**	
· **Melting point/freezing point:**	Undetermined.
· **Initial boiling point and boiling range:**	77 °C
· **Flash point:**	-4 °C
· **Flammability (solid, gas):**	Not applicable.
· **Ignition temperature:**	405 °C
· **Decomposition temperature:**	Not determined.
· **Auto-ignition temperature:**	Product is not selfigniting.
· **Explosive properties:**	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· **Explosion limits:**	
· **Lower:**	1.2 Vol %
· **Upper:**	11.5 Vol %
· **Vapour pressure at 20 °C:**	97 hPa
· **Density at 20 °C:**	0.968 g/cmj
· **Relative density**	Not determined.
· **Vapour density**	Not determined.
· **Evaporation rate**	Not determined.
· **Solubility in / Miscibility with**	
· **water:**	Not miscible or difficult to mix.
· **Partition coefficient: n-octanol/water:**	Not determined.
· **Viscosity:**	
· **Dynamic:**	Not determined.
· **Kinematic at 20 °C:**	40 s (ISO 4 mm)
· **Oxidising properties :**	N.A.

(Contd. on page 8)

Safety data sheet
as per regulation 1907/2006/EC (REACH) as amended and supplemented

Product code LNB837
Trade name: POLYURETHANE HARDENER

(Contd. of page 7)

· **Solvent content:**
· **VOC and Total VOC**
(organic solvents + reactive solvents if any) 70.00 %
· **VOC (EC)** 677.6 g/l

· **Solids content:** 29.9 %
· **9.2 Other information** No further relevant information available.

SECTION 10: Stability and reactivity

· **10.1 Reactivity** Typical of the product as indicated in the data sheet
· **10.2 Chemical stability**
The product is stable in normal conditions of storage and use recommended
· **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
· **10.3 Possibility of hazardous reactions**
Reacts with strong acids and oxidising agents.
Vapours may form explosive mixtures with air
· **10.4 Conditions to avoid** No further relevant information available.
· **10.5 Incompatible materials:** No further relevant information available.
· **10.6 Hazardous decomposition products:**

In case of possible formation of combustion:
Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information

· **11.1 Information on toxicological effects**
· **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

108-88-3 toluene		
Oral	LD50	5,000 mg/kg (mouse)
Dermal	LD50	12,124 mg/kg (rabbit)
Inhalative	LC50/4 h	25.7 mg/l (mouse)
53317-61-6 Aromatic polyisocyanate		
Oral	LD50	5,001 mg/kg (mouse)
110-19-0 isobutyl acetate		
Oral	LD50	13,400 mg/kg (mouse)
Dermal	LD50	17,401 mg/kg (rabbit)
Inhalative	LC50/4 h	31 mg/l (mouse)
141-78-6 ethyl acetate		
Oral	LD50	4,934 mg/kg (rabbit)
Dermal	LD50	20,001 mg/kg (rabbit)
Inhalative	LC50/4 h	1,600 mg/l (mouse)
	LC0	22.6 ppm (mouse)
26471-62-5 m-tolylidene diisocyanate		
Oral	LD50	5,110 mg/kg (mouse)

(Contd. on page 9)

(Contd. of page 8)

Dermal	LD50	9,401 mg/kg (rabbit)
Inhalative	LC50/4 h	0.107 mg/l (mouse)

· **Primary irritant effect:**
· **Skin corrosion/irritation**
Causes skin irritation.
· **Serious eye damage/irritation**
Causes serious eye irritation.
· **Respiratory or skin sensitisation**
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause an allergic skin reaction.
· **Sensitisation**
Toluene-diisocyanate (mixture of isomers)
Skin sensitization (LLNA - Local Lymph Node Assay): mouse
positive Result
Method OECD TG 429

Respiratory sensitization
May cause sensitization by inhalation
· **CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)**
· **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
· **Carcinogenicity** Based on available data, the classification criteria are not met.
· **Reproductive toxicity**
Suspected of damaging the unborn child.
· **STOT-single exposure**
May cause drowsiness or dizziness.
· **STOT-repeated exposure**
May cause damage to organs through prolonged or repeated exposure.
· **Aspiration hazard**
May be fatal if swallowed and enters airways.

· **More information**
Monomers / polymers isocyanate
Particular characteristics / effects; Over-exposure there is a danger, as a function of concentration, irritation of the eyes, nose, throat and respiratory tract.
Possible the delayed appearance of disorders and development of a form of hypersensitivity (respiratory disorders, cough, asthma). In the case of persons hypersensitive reactions may occur already at concentrations of isocyanate very low, even below the TLV value. In case of prolonged contact with the skin are possible irritant effects and dehydrating.

SECTION 12: Ecological information

· **12.1 Toxicity** Harmful to aquatic life with long lasting effects.

· **Aquatic toxicity:**	
108-88-3 toluene	
EC50	134 mg/l (algae) (96 h)
	3.78 mg/l (daphnia) (48 h)
LC50 (96h)	5.5 mg/l (Fish)
110-19-0 isobutyl acetate	
EC50	370 mg/l (algae) (72 h)
	25 mg/l (daphnia)
LC50 (96h)	17 mg/l (Fish)

(Contd. on page 10)

(Contd. of page 9)

141-78-6 ethyl acetate	
EC50	165 mg/l (daphnia) (48 h)
LC50 (96h)	230 mg/l (Fish)
26471-62-5 m-tolylidene diisocyanate	
EC50	12.5 mg/l (daphnia) (48h)
LC50 (96h)	133 mg/l (Leuciscus idus melanotus)

· **12.2 Persistence and degradability** No further relevant information available.
· **12.3 Bioaccumulative potential** No further relevant information available.
· **12.4 Mobility in soil** No further relevant information available.
· **Ecotoxical effects:**
· **Remark:** Harmful to fish
· **Additional ecological information:**
· **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Harmful to aquatic organisms
· **12.5 Results of PBT and vPvB assessment**
· **PBT:** Not applicable.
· **vPvB:** Not applicable.
· **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**
· **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
Hand over to hazardous waste disposers.
The code number of the product as is 080111

· **Uncleaned packaging:**
· **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

· **14.1 UN-Number**
· **ADR, IMDG, IATA** UN1263

· **14.2 UN proper shipping name**
· **ADR, IMDG, IATA** PAINT

· **14.3 Transport hazard class(es)**

· **ADR, IMDG, IATA**



· **Class** 3 Flammable liquids.
· **Label** 3

(Contd. on page 11)

Safety data sheet
as per regulation 1907/2006/EC (REACH) as amended and supplemented

Printing date 17.10.2019 *Version number 166* *Revision: 17.10.2019*

Product code LNB837
Trade name: POLYURETHANE HARDENER

(Contd. of page 10)

· **14.4 Packing group**
· **ADR, IMDG, IATA** II

· **14.5 Environmental hazards:**
· **Marine pollutant:** No

· **14.6 Special precautions for user** Warning: Flammable liquids.
· **Danger code (Kemler):** 33
· **EMS Number:** F-E,S-E
· **Stowage Category** B

· **14.7 Transport in bulk according to Annex II of Marpol and the IBC Code** Not applicable.

· **Transport/Additional information:**

· **ADR**
· **Limited quantities (LQ)** 5L
· **Excepted quantities (EQ)** Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml
· **Transport category** 2
· **Tunnel restriction code** D/E

· **IMDG**
· **Limited quantities (LQ)** 5L
· **Excepted quantities (EQ)** Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml

· **UN "Model Regulation":** UN 1263 PAINT, 3, II

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
Directive n. : 80/1107/CEE, n. 82/605/CEE, n. 83/477/CEE, n. 86/188/CEE e n. 88/642/CEE, 89/391/CEE, 89/654/CEE, 89/655/CEE, 89/656/CEE, 90/269/CEE, 90/270/CEE, 90/394/CEE, 90/679/CEE, 93/88/CEE, 95/63/CE, 97/42/CE, 98/24/CE, 99/38/CE, 99/92/CE, 2001/45/CE, 2002/44,2003/10/CE, 2003/18/CE , 2004/40/CE,2006/25
DIRECTIVE 2012/18/EU
P5c Flammable Limit 1: 5000 t
Limit 2: 50000 t
· **Various regulations** For uses not regulated by D. 2004/42/EC-For professional use only
· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t
· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t
· **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3, 48

· **National regulations:**
The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

(Contd. on page 12)

Safety data sheet
as per regulation 1907/2006/EC (REACH) as amended and supplemented

Printing date 17.10.2019 *Version number 166* *Revision: 17.10.2019*

Product code LNB837
Trade name: POLYURETHANE HARDENER

(Contd. of page 11)

· ***15.2 Chemical safety assessment:*** *A Chemical Safety Assessment has not been carried out.*

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· ***Relevant phrases***
H225 Highly flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H330 Fatal if inhaled.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H351 Suspected of causing cancer.
H361d Suspected of damaging the unborn child.
H373 May cause damage to organs through prolonged or repeated exposure.
H412 Harmful to aquatic life with long lasting effects.

· ***Department issuing SDS:*** *IVM Chemicals Srl*
· ***Contact:*** *Claudia Zanella*
· ***Abbreviations and acronyms:***
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 2: Flammable liquids ï Category 2
Acute Tox. 2: Acute toxicity ï Category 2
Skin Irrit. 2: Skin corrosion/irritation ï Category 2
Eye Irrit. 2: Serious eye damage/eye irritation ï Category 2
Resp. Sens. 1: Respiratory sensitisation ï Category 1
Skin Sens. 1: Skin sensitisation ï Category 1
Carc. 2: Carcinogenicity ï Category 2
Repr. 2: Reproductive toxicity ï Category 2
STOT SE 3: Specific target organ toxicity (single exposure) ï Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) ï Category 2
Asp. Tox. 1: Aspiration hazard ï Category 1
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard ï Category 3
· ***Sources***
REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments
Agency ECHA web site
INRS Fiche Toxicologique
· **** Data compared to the previous version altered.***