W: www.electacolor.com
M: info@electacolor.com
P: +39 0432 74 60 61
F: +39 0432 74 39 81

CAT070

23/04/2024 Rev.1

Name and Code: CAT070 PU NY Hardener .

Chemical Nature: Polyisocyanic hardener.

Description and performances:

Polyisocyanate for PU basecoats and topcoats that shows good elasticity, good body, good wetting and pot-life. Common hardener for matt pigmented PU (light color). It has good light fastness and it is fast drying.

Additional description of the product:

Chemical - Technical Properties

Description	Method	Unit of measure	Value - Range
Solid content(*)	I.O. 371	%	24±1
Specific gravity(*)	I.O. 309	g/cm3	0,94±0,02

* Typical values
Danger level for people and environment
Before use consult the safety data sheet.

Storage instructions:

Keep the product in a ventilated area; do not exceed 25-28°C. Polyisocyanic hardeners should be
protected from frost and humidity. If they have been partially used please close the can tigth and use
the residual amount in a short time.
EXPIRATION DATE: 12 months
The data refers to the product stored in original sealed packaging.

The information provided in this data sheet is based on the best of our knowledge and experience. Electa Color Coatings guarantees the constancy of the chemical-physical characteristics of its products within the tolerances shown above. The final result will fall under the total responsibility of the user who must verify that the product meets their needs in terms of safety and equipment application, material to be painted and environmental conditions before using it. The technical network Electa Color Coatings sales representative is at your complete disposal to clarify any problems regarding the application correct of our products.