W: www.electacolor.com
M: info@electacolor.com
P: +39 0432 74 60 61
F: +39 0432 74 39 81

**UVA099**

**24/10/2017 Rev.1**

**Name and Code:** UVA099 Clear ACR UV Sealer SP .

**Chemical Nature:** UV-curable paint.

**Description and performances:**

Photoinitiated UV curing basecoat, ready to use

**Additional description of the product**

Chemical - Technical Properties

| Description | Method | Unit of measure | Value - Range |
|---|---|---|---|
| Solid content | I.O. 371 | % | 33±1 |
| Viscosity DIN 4 @20°C | I.O. 301 | seconds | 22±3 |
| Specific gravity | I.O. 309 | g/cm3 | 0,945±0,010 |

**Field of application:**

UVA099 : ready to use
DTL305 : 50 parts by weight maximum, if needed

Application amount: 60-90 g/m²
Number of layers: 1.
Application devices: spray grade.

Drying conditions: 40 °C, 4-6 minutes.
TLM 03-10: 1 minutes.
UV lamp: 360nm, 80 W/cm² ( 2 )
Line speed: 8 m/min.

**General properties:**

UV curable polyacrylic basecoat with great wetting properties and reactivity. Product is already photoinitiated and diluted
The product has good hiding power, sandability and it is suitable for the finishing of flat items.

W: www.electacolor.com
M: info@electacolor.com
P: +39 0432 74 60 61
F: +39 0432 74 39 81



**Storage instructions:**

Keep the paint in a ventilated area; do not exceed 25-28°C.
EXPIRATION DATE: 6 months
The data refers to the product stored in original sealed packaging.

The information provided in this data sheet is based on the best of our knowledge and experience. Electa Color Coatings guarantees the constancy of the chemical-physical characteristics of its products within the tolerances shown above. The final result will fall under the total responsibility of the user who must verify that the product meets their needs in terms of safety and equipment application, material to be painted and environmental conditions before using it. The technical network Electa Color Coatings sales representative is at your complete disposal to clarify any problems regarding the application correct of our products.